

KATO KA-1300R ブーム定格総荷重表 (SLジブ無)

| NA1性能 作業半径 (m) | アウトリガ最大 (8.4m) 張出 (全周) | | | | | | カウンタウエイト 24t | |
|----------------------|------------------------|--------------|---------------|--------------|--------------|--------------|--------------|--|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム | |
| 2.5 | 70.0 | | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | | |
| 4.5 | 70.0 | 50.0 | 35.0 | | | | | |
| 5.0 | 70.0 | 50.0 | 35.0 | 24.0 | | | | |
| 6.0 | 67.3 | 50.0 | 35.0 | 24.0 | | | | |
| 7.0 | 58.9 | 50.0 | 35.0 | 24.0 | 17.0 | 14.0 | | |
| 8.0 | 50.6 | 49.7 | 35.0 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 9.0 | 44.1 | 43.2 | 35.0 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 10.0 | | 38.0 | 33.7 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 12.0 | | 30.2 | 27.8 | 23.2 | 17.0 | 14.0 | 12.0 | |
| 14.0 | | 24.6 | 23.4 | 20.7 | 15.8 | 14.0 | 12.0 | |
| 16.0 | | 20.4 | 20.0 | 18.4 | 14.0 | 14.0 | 12.0 | |
| 18.0 | | | 16.4 | 16.3 | 12.6 | 13.1 | 12.0 | |
| 20.0 | | | 13.5 | 14.2 | 11.5 | 11.7 | 11.0 | |
| 22.0 | | | 11.1 | 12.5 | 10.5 | 10.4 | 9.8 | |
| 24.0 | | | 9.2 | 10.6 | 9.6 | 9.3 | 8.8 | |
| 26.0 | | | | 9.1 | 8.9 | 8.4 | 7.9 | |
| 28.0 | | | | 7.8 | 8.1 | 7.6 | 7.1 | |
| 30.0 | | | | 6.6 | 7.4 | 6.9 | 6.5 | |
| 32.0 | | | | 5.7 | 6.5 | 6.3 | 5.9 | |
| 34.0 | | | | | 5.7 | 5.7 | 5.3 | |
| 36.0 | | | | | 4.9 | 5.2 | 4.9 | |
| 38.0 | | | | | 4.1 | 4.5 | 4.5 | |
| 40.0 | | | | | 3.4 | 3.8 | 4.1 | |
| 42.0 | | | | | 1.4 | 3.2 | 3.5 | |
| 44.0 | | | | | | 2.6 | 2.9 | |
| 46.0 | | | | | | | 2.4 | |
| 48.0 | | | | | | | 2.0 | |
| 危険角度(°) | — | — | — | — | — | 11 | 16 | |
| 標準フック | 70t | 50t | | | | | | |
| フック質量 | 900kg | 600kg | | | | | | |
| 巻掛本数 | 10 | 7 | 5 | 4 | | | | |

(単位 : ton)

KATO KA-1300R ブーム定格総荷重表 (SLジブ無)



| NA2性能 作業半径 (m) | アウトリガ中間 (7.4m) 張出 (側方) | | | | | | カウンタウエイト 24t | | |
|----------------------|------------------------|--------------|---------------|--------------|--------------|--------------|--------------|--|--|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム | | |
| 2.5 | 70.0 | | | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | | | |
| 4.5 | 70.0 | 50.0 | 35.0 | | | | | | |
| 5.0 | 70.0 | 50.0 | 35.0 | 24.0 | | | | | |
| 6.0 | 64.4 | 50.0 | 35.0 | 24.0 | | | | | |
| 7.0 | 56.5 | 50.0 | 35.0 | 24.0 | 17.0 | 14.0 | | | |
| 8.0 | 50.2 | 49.3 | 35.0 | 24.0 | 17.0 | 14.0 | 12.0 | | |
| 9.0 | 44.1 | 43.2 | 35.0 | 24.0 | 17.0 | 14.0 | 12.0 | | |
| 10.0 | | 38.0 | 33.7 | 24.0 | 17.0 | 14.0 | 12.0 | | |
| 12.0 | | 29.1 | 27.8 | 23.2 | 17.0 | 14.0 | 12.0 | | |
| 14.0 | | 22.0 | 21.8 | 20.7 | 15.8 | 14.0 | 12.0 | | |
| 16.0 | | 17.2 | 17.0 | 18.4 | 14.0 | 14.0 | 12.0 | | |
| 18.0 | | | 13.5 | 14.9 | 12.6 | 13.1 | 12.0 | | |
| 20.0 | | | 10.9 | 12.3 | 11.5 | 11.7 | 11.0 | | |
| 22.0 | | | 8.9 | 10.2 | 10.5 | 10.4 | 9.8 | | |
| 24.0 | | | 7.2 | 8.5 | 9.3 | 9.3 | 8.8 | | |
| 26.0 | | | | 7.2 | 8.0 | 8.3 | 7.9 | | |
| 28.0 | | | | 6.0 | 6.8 | 7.2 | 7.1 | | |
| 30.0 | | | | 5.1 | 5.8 | 6.2 | 6.4 | | |
| 32.0 | | | | 4.1 | 5.0 | 5.3 | 5.5 | | |
| 34.0 | | | | | 4.3 | 4.6 | 4.8 | | |
| 36.0 | | | | | 3.5 | 3.9 | 4.2 | | |
| 38.0 | | | | | 2.8 | 3.2 | 3.5 | | |
| 40.0 | | | | | 2.2 | 2.6 | 2.9 | | |
| 42.0 | | | | | 1.4 | 2.1 | 2.4 | | |
| 44.0 | | | | | | 1.6 | 1.9 | | |
| 46.0 | | | | | | | 1.4 | | |
| 危険角度(°) | — | — | — | — | — | 20 | 25 | | |
| 標準フック | 70t | 50t | | | | | | | |
| フック質量 | 900kg | 600kg | | | | | | | |
| 巻掛本数 | 10 | 7 | 5 | 4 | | | | | |

(単位 : ton)

NA性能

NB性能

NC性能

ND性能

NE性能

SLジブ横抱

SLジブ無

KATO KA-1300R ブーム定格総荷重表 (SLジブ無)

| NA3性能 | | アウトリガ中間 (6.4m) 張出 (側方) | | | | | カウンタウエイト 24t | |
|----------|--------------|------------------------|---------------|--------------|--------------|--------------|--------------|--|
| 作業半径 (m) | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム | |
| 2.5 | 70.0 | | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | | |
| 4.5 | 70.0 | 50.0 | 35.0 | | | | | |
| 5.0 | 70.0 | 50.0 | 35.0 | 24.0 | | | | |
| 6.0 | 60.9 | 50.0 | 35.0 | 24.0 | | | | |
| 7.0 | 53.3 | 50.0 | 35.0 | 24.0 | 17.0 | 14.0 | | |
| 8.0 | 47.1 | 46.2 | 35.0 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 9.0 | 40.6 | 39.5 | 35.0 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 10.0 | | 32.6 | 32.6 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 12.0 | | 23.6 | 23.4 | 23.2 | 17.0 | 14.0 | 12.0 | |
| 14.0 | | 17.9 | 17.7 | 19.1 | 15.8 | 14.0 | 12.0 | |
| 16.0 | | 13.9 | 13.7 | 15.1 | 14.0 | 14.0 | 12.0 | |
| 18.0 | | | 10.8 | 12.1 | 12.6 | 13.1 | 12.0 | |
| 20.0 | | | 8.6 | 9.9 | 10.7 | 11.1 | 11.0 | |
| 22.0 | | | 6.8 | 8.1 | 8.9 | 9.3 | 9.5 | |
| 24.0 | | | 5.4 | 6.7 | 7.5 | 7.9 | 8.1 | |
| 26.0 | | | | 5.5 | 6.3 | 6.7 | 6.9 | |
| 28.0 | | | | 4.5 | 5.3 | 5.6 | 5.9 | |
| 30.0 | | | | 3.5 | 4.5 | 4.8 | 5.0 | |
| 32.0 | | | | 2.6 | 3.6 | 4.1 | 4.3 | |
| 34.0 | | | | | 2.9 | 3.3 | 3.6 | |
| 36.0 | | | | | 2.2 | 2.6 | 2.9 | |
| 38.0 | | | | | 1.6 | 2.0 | 2.3 | |
| 40.0 | | | | | 1.1 | 1.5 | 1.8 | |
| 42.0 | | | | | | | 1.3 | |
| 危険角度(°) | — | — | — | — | 20 | 32 | 35 | |
| 標準フック | 70t | | | | 50t | | | |
| フック質量 | 900kg | | | | 600kg | | | |
| 巻掛本数 | 10 | 7 | 5 | | | 4 | | |

(単位 : ton)

| NA4性能 | | アウトリガ中間 (5.4m) 張出 (側方) | | | | | カウンタウエイト 24t | |
|----------|--------------|------------------------|---------------|--------------|--------------|--------------|--------------|--|
| 作業半径 (m) | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム | |
| 2.5 | 70.0 | | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | | |
| 4.5 | 70.0 | 50.0 | 35.0 | | | | | |
| 5.0 | 66.2 | 50.0 | 35.0 | 24.0 | | | | |
| 6.0 | 56.8 | 50.0 | 35.0 | 24.0 | | | | |
| 7.0 | 46.6 | 45.6 | 35.0 | 24.0 | 17.0 | 14.0 | | |
| 8.0 | 36.7 | 35.8 | 35.0 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 9.0 | 30.0 | 29.0 | 29.0 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 10.0 | | 24.1 | 24.1 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 12.0 | | 17.5 | 17.4 | 18.7 | 17.0 | 14.0 | 12.0 | |
| 14.0 | | 13.2 | 13.0 | 14.3 | 15.1 | 14.0 | 12.0 | |
| 16.0 | | 10.2 | 10.0 | 11.2 | 12.0 | 12.4 | 12.0 | |
| 18.0 | | | 7.7 | 8.9 | 9.7 | 10.0 | 10.3 | |
| 20.0 | | | 6.0 | 7.2 | 7.9 | 8.3 | 8.5 | |
| 22.0 | | | 4.6 | 5.8 | 6.5 | 6.8 | 7.0 | |
| 24.0 | | | 3.4 | 4.6 | 5.3 | 5.7 | 5.9 | |
| 26.0 | | | | 3.7 | 4.4 | 4.7 | 4.9 | |
| 28.0 | | | | 2.8 | 3.6 | 3.9 | 4.1 | |
| 30.0 | | | | 1.9 | 2.9 | 3.2 | 3.4 | |
| 32.0 | | | | 1.2 | 2.2 | 2.6 | 2.8 | |
| 34.0 | | | | | 1.5 | 1.9 | 2.2 | |
| 36.0 | | | | | | 1.3 | 1.6 | |
| 38.0 | | | | | | | 1.1 | |
| 危険角度(°) | — | — | — | — | 37 | 40 | 42 | |
| 標準フック | 70t | | | | 50t | | | |
| フック質量 | 900kg | | | | 600kg | | | |
| 巻掛本数 | 10 | 7 | 5 | | | 4 | | |

(単位 : ton)

KATO KA-1300R ブーム定格総荷重表 (SLジブ無)



| NA5性能 作業半径 (m) | アウトリガ中間 (4.4m) 張出 (側方) | | | | | | カウンタウエイト 24t | | |
|----------------------|------------------------|--------------|---------------|--------------|--------------|--------------|--------------|--|--|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム | | |
| 2.5 | 70.0 | | | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | | | |
| 4.5 | 66.2 | 50.0 | 35.0 | | | | | | |
| 5.0 | 60.7 | 50.0 | 35.0 | 24.0 | | | | | |
| 6.0 | 46.1 | 45.1 | 35.0 | 24.0 | | | | | |
| 7.0 | 35.3 | 34.3 | 34.5 | 24.0 | 17.0 | 14.0 | | | |
| 8.0 | 28.3 | 27.3 | 27.3 | 24.0 | 17.0 | 14.0 | 12.0 | | |
| 9.0 | 23.3 | 22.3 | 22.3 | 23.6 | 17.0 | 14.0 | 12.0 | | |
| 10.0 | | 18.6 | 18.5 | 19.8 | 17.0 | 14.0 | 12.0 | | |
| 12.0 | | 13.4 | 13.3 | 14.5 | 15.3 | 14.0 | 12.0 | | |
| 14.0 | | 10.0 | 9.8 | 11.0 | 11.8 | 12.2 | 12.0 | | |
| 16.0 | | 7.6 | 7.3 | 8.5 | 9.2 | 9.6 | 9.9 | | |
| 18.0 | | | 5.5 | 6.6 | 7.4 | 7.7 | 7.9 | | |
| 20.0 | | | 4.0 | 5.2 | 5.9 | 6.2 | 6.5 | | |
| 22.0 | | | 2.6 | 4.0 | 4.7 | 5.1 | 5.3 | | |
| 24.0 | | | 1.4 | 3.0 | 3.8 | 4.1 | 4.3 | | |
| 26.0 | | | | 2.0 | 3.0 | 3.3 | 3.5 | | |
| 28.0 | | | | 1.1 | 2.1 | 2.6 | 2.8 | | |
| 30.0 | | | | | 1.4 | 1.8 | 2.1 | | |
| 32.0 | | | | | | 1.1 | 1.4 | | |
| 危険角度(°) | — | — | — | 36 | 45 | 47 | 51 | | |
| 標準フック | 70t | 50t | | | | | | | |
| フック質量 | 900kg | 600kg | | | | | | | |
| 巻掛本数 | 10 | 7 | 5 | 4 | | | | | |

(単位 : ton)

NA性能
NB性能
NC性能
ND性能
NE性能

SLジブ横抱
SLジブ無

KATO KA-1300R ブーム定格総荷重表 (SLジブ無)

| NB1性能 作業半径 (m) | アウトリガ最大 (8.4m) 張出 (全周) | | | | | | カウンタウエイト 16t | | |
|----------------------|------------------------|--------------|---------------|--------------|--------------|--------------|--------------|--|--|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム | | |
| 2.5 | 70.0 | | | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | | | |
| 4.5 | 70.0 | 50.0 | 35.0 | | | | | | |
| 5.0 | 70.0 | 50.0 | 35.0 | 24.0 | | | | | |
| 6.0 | 66.6 | 50.0 | 35.0 | 24.0 | | | | | |
| 7.0 | 56.1 | 50.0 | 35.0 | 24.0 | 17.0 | 14.0 | | | |
| 8.0 | 48.1 | 47.2 | 35.0 | 24.0 | 17.0 | 14.0 | 12.0 | | |
| 9.0 | 41.9 | 41.0 | 35.0 | 24.0 | 17.0 | 14.0 | 12.0 | | |
| 10.0 | | 36.0 | 33.7 | 24.0 | 17.0 | 14.0 | 12.0 | | |
| 12.0 | | 28.6 | 27.8 | 23.2 | 17.0 | 14.0 | 12.0 | | |
| 14.0 | | 22.3 | 21.8 | 20.7 | 15.8 | 14.0 | 12.0 | | |
| 16.0 | | 17.5 | 17.1 | 18.4 | 14.0 | 14.0 | 12.0 | | |
| 18.0 | | | 13.7 | 15.2 | 12.6 | 13.1 | 12.0 | | |
| 20.0 | | | 11.1 | 12.6 | 11.5 | 11.7 | 11.0 | | |
| 22.0 | | | 9.0 | 10.5 | 10.5 | 10.4 | 9.8 | | |
| 24.0 | | | 7.3 | 8.8 | 9.6 | 9.3 | 8.8 | | |
| 26.0 | | | | 7.4 | 8.2 | 8.4 | 7.9 | | |
| 28.0 | | | | 6.1 | 7.0 | 7.3 | 7.1 | | |
| 30.0 | | | | 4.9 | 6.0 | 6.3 | 6.5 | | |
| 32.0 | | | | 3.9 | 5.0 | 5.3 | 5.6 | | |
| 34.0 | | | | | 4.1 | 4.4 | 4.7 | | |
| 36.0 | | | | | 3.3 | 3.7 | 4.0 | | |
| 38.0 | | | | | 2.6 | 3.0 | 3.3 | | |
| 40.0 | | | | | 2.0 | 2.4 | 2.7 | | |
| 42.0 | | | | | 1.4 | 1.8 | 2.1 | | |
| 44.0 | | | | | | 1.3 | 1.6 | | |
| 46.0 | | | | | | | 1.2 | | |
| 危険角度(°) | — | — | — | — | — | 16 | 22 | | |
| 標準フック | 70t | 50t | | | | | | | |
| フック質量 | 900kg | 600kg | | | | | | | |
| 巻掛本数 | 10 | 7 | 5 | 4 | | | | | |

(単位 : ton)

KATO KA-1300R ブーム定格総荷重表 (SLジブ無)



| NB2性能 作業半径 (m) | アウトリガ中間 (7.4m) 張出 (側方) | | | | | | カウンタウエイト 16t | |
|----------------------|------------------------|--------------|---------------|--------------|--------------|--------------|--------------|--|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム | |
| 2.5 | 70.0 | | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | | |
| 4.5 | 70.0 | 50.0 | 35.0 | | | | | |
| 5.0 | 70.0 | 50.0 | 35.0 | 24.0 | | | | |
| 6.0 | 63.5 | 50.0 | 35.0 | 24.0 | | | | |
| 7.0 | 55.7 | 50.0 | 35.0 | 24.0 | 17.0 | 14.0 | | |
| 8.0 | 48.1 | 47.2 | 35.0 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 9.0 | 41.9 | 41.0 | 35.0 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 10.0 | | 34.5 | 33.7 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 12.0 | | 24.4 | 24.0 | 23.2 | 17.0 | 14.0 | 12.0 | |
| 14.0 | | 18.3 | 17.8 | 19.5 | 15.8 | 14.0 | 12.0 | |
| 16.0 | | 14.1 | 13.7 | 15.3 | 14.0 | 14.0 | 12.0 | |
| 18.0 | | | 10.7 | 12.2 | 12.6 | 13.1 | 12.0 | |
| 20.0 | | | 8.4 | 9.9 | 10.8 | 11.0 | 11.0 | |
| 22.0 | | | 6.7 | 8.1 | 8.9 | 9.2 | 9.4 | |
| 24.0 | | | 5.2 | 6.6 | 7.4 | 7.7 | 8.0 | |
| 26.0 | | | | 5.4 | 6.2 | 6.5 | 6.7 | |
| 28.0 | | | | 4.4 | 5.2 | 5.5 | 5.7 | |
| 30.0 | | | | 3.3 | 4.4 | 4.6 | 4.9 | |
| 32.0 | | | | 2.5 | 3.5 | 3.9 | 4.1 | |
| 34.0 | | | | | 2.7 | 3.1 | 3.4 | |
| 36.0 | | | | | 2.1 | 2.4 | 2.7 | |
| 38.0 | | | | | 1.5 | 1.8 | 2.1 | |
| 40.0 | | | | | | 1.3 | 1.6 | |
| 42.0 | | | | | | | 1.1 | |
| 危険角度(°) | — | — | — | — | 28 | 32 | 35 | |
| 標準フック | 70t | | | | 50t | | | |
| フック質量 | 900kg | | | | 600kg | | | |
| 巻掛本数 | 10 | 7 | 5 | | | 4 | | |

(単位 : ton)

NA性能

NB性能

NC性能

ND性能

NE性能

SLジブ横抱

SLジブ無

KATO KA-1300R ブーム定格総荷重表 (SLジブ無)

| NB3性能 作業半径 (m) | アウトリガ中間 (6.4m) 張出 (側方) | | | | | | カウンタウエイト 16t | | |
|----------------------|------------------------|--------------|---------------|--------------|--------------|--------------|--------------|-------|--|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム | | |
| 2.5 | 70.0 | | | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | | | |
| 4.5 | 70.0 | 50.0 | 35.0 | | | | | | |
| 5.0 | 69.5 | 50.0 | 35.0 | 24.0 | | | | | |
| 6.0 | 59.9 | 50.0 | 35.0 | 24.0 | | | | | |
| 7.0 | 52.3 | 50.0 | 35.0 | 24.0 | 17.0 | 14.0 | | | |
| 8.0 | 42.8 | 41.9 | 35.0 | 24.0 | 17.0 | 14.0 | 12.0 | | |
| 9.0 | 34.4 | 33.5 | 33.0 | 24.0 | 17.0 | 14.0 | 12.0 | | |
| 10.0 | | 27.5 | 27.1 | 24.0 | 17.0 | 14.0 | 12.0 | | |
| 12.0 | | 19.6 | 19.2 | 20.9 | 17.0 | 14.0 | 12.0 | | |
| 14.0 | | 14.6 | 14.2 | 15.8 | 15.8 | 14.0 | 12.0 | | |
| 16.0 | | 11.2 | 10.8 | 12.3 | 13.2 | 13.5 | 12.0 | | |
| 18.0 | | | 8.3 | 9.7 | 10.6 | 10.9 | 11.1 | | |
| 20.0 | | | 6.4 | 7.8 | 8.6 | 8.9 | 9.1 | | |
| 22.0 | | | 4.8 | 6.2 | 7.1 | 7.3 | 7.6 | | |
| 24.0 | | | 3.3 | 5.0 | 5.8 | 6.1 | 6.3 | | |
| 26.0 | | | | 3.8 | 4.8 | 5.0 | 5.3 | | |
| 28.0 | | | | 2.8 | 3.8 | 4.2 | 4.4 | | |
| 30.0 | | | | 1.9 | 2.9 | 3.3 | 3.6 | | |
| 32.0 | | | | 1.1 | 2.1 | 2.5 | 2.8 | | |
| 34.0 | | | | | 1.5 | 1.8 | 2.1 | | |
| 36.0 | | | | | | 1.2 | 1.5 | | |
| 危険角度(°) | — | — | — | — | 38 | 40 | 45 | | |
| 標準フック | 70t | | | | | | | 50t | |
| フック質量 | 900kg | | | | | | | 600kg | |
| 巻掛本数 | 10 | 7 | 5 | | | | | 4 | |

(単位 : ton)

| NB4性能 作業半径 (m) | アウトリガ中間 (5.4m) 張出 (側方) | | | | | | カウンタウエイト 16t | | |
|----------------------|------------------------|--------------|---------------|--------------|--------------|--------------|--------------|-------|--|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム | | |
| 2.5 | 70.0 | | | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | | | |
| 4.5 | 70.0 | 50.0 | 35.0 | | | | | | |
| 5.0 | 64.8 | 50.0 | 35.0 | 24.0 | | | | | |
| 6.0 | 53.0 | 50.0 | 35.0 | 24.0 | | | | | |
| 7.0 | 39.4 | 38.7 | 35.0 | 24.0 | 17.0 | 14.0 | | | |
| 8.0 | 30.9 | 30.1 | 29.8 | 24.0 | 17.0 | 14.0 | 12.0 | | |
| 9.0 | 25.1 | 24.3 | 23.9 | 24.0 | 17.0 | 14.0 | 12.0 | | |
| 10.0 | | 20.0 | 19.7 | 21.3 | 17.0 | 14.0 | 12.0 | | |
| 12.0 | | 14.3 | 13.9 | 15.4 | 16.3 | 14.0 | 12.0 | | |
| 14.0 | | 10.5 | 10.2 | 11.6 | 12.4 | 12.7 | 12.0 | | |
| 16.0 | | 7.9 | 7.6 | 8.9 | 9.7 | 10.0 | 10.2 | | |
| 18.0 | | | 5.6 | 6.9 | 7.7 | 8.0 | 8.2 | | |
| 20.0 | | | 4.1 | 5.4 | 6.2 | 6.4 | 6.6 | | |
| 22.0 | | | 2.7 | 4.2 | 4.9 | 5.2 | 5.4 | | |
| 24.0 | | | 1.4 | 3.2 | 3.9 | 4.2 | 4.4 | | |
| 26.0 | | | | 2.1 | 3.1 | 3.4 | 3.6 | | |
| 28.0 | | | | 1.2 | 2.3 | 2.6 | 2.9 | | |
| 30.0 | | | | | 1.5 | 1.9 | 2.1 | | |
| 32.0 | | | | | | 1.2 | 1.5 | | |
| 危険角度(°) | — | — | — | 36 | 46 | 47 | 51 | | |
| 標準フック | 70t | | | | | | | 50t | |
| フック質量 | 900kg | | | | | | | 600kg | |
| 巻掛本数 | 10 | 7 | 5 | | | | | 4 | |

(単位 : ton)

KATO KA-1300R ブーム定格総荷重表 (SLジブ無)



| NB5性能 作業半径 (m) | アウトリガ中間 (4.4m) 張出 (側方) | | | | | | カウンタウエイト 16t | |
|----------------------|------------------------|--------------|---------------|--------------|--------------|--------------|--------------|--|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム | |
| 2.5 | 70.0 | | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | | |
| 4.5 | 64.6 | 50.0 | 35.0 | | | | | |
| 5.0 | 54.5 | 50.0 | 35.0 | 24.0 | | | | |
| 6.0 | 38.7 | 38.1 | 35.0 | 24.0 | | | | |
| 7.0 | 29.4 | 28.8 | 28.4 | 24.0 | 17.0 | 14.0 | | |
| 8.0 | 23.4 | 22.7 | 22.3 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 9.0 | 19.1 | 18.3 | 18.0 | 19.6 | 17.0 | 14.0 | 12.0 | |
| 10.0 | | 15.1 | 14.8 | 16.3 | 17.0 | 14.0 | 12.0 | |
| 12.0 | | 10.6 | 10.3 | 11.7 | 12.6 | 12.9 | 12.0 | |
| 14.0 | | 7.7 | 7.3 | 8.7 | 9.5 | 9.8 | 10.0 | |
| 16.0 | | 5.6 | 5.2 | 6.5 | 7.3 | 7.6 | 7.8 | |
| 18.0 | | | 3.6 | 4.9 | 5.7 | 5.9 | 6.1 | |
| 20.0 | | | 2.0 | 3.6 | 4.4 | 4.6 | 4.9 | |
| 22.0 | | | | 2.5 | 3.4 | 3.6 | 3.8 | |
| 24.0 | | | | 1.4 | 2.4 | 2.8 | 3.0 | |
| 26.0 | | | | | 1.5 | 1.9 | 2.2 | |
| 危険角度(°) | — | — | 41 | 46 | 53 | 56 | 59 | |
| 標準フック | 70t | | | | 50t | | | |
| フック質量 | 900kg | | | | 600kg | | | |
| 巻掛本数 | 10 | 7 | 5 | | | 4 | | |

(単位 : ton)

NA性能

NB性能

NC性能

ND性能

NE性能

| NB6性能 作業半径 (m) | アウトリガ最小 (3.4m) 張出 (側方) | | | | | | カウンタウエイト 16t | |
|----------------------|------------------------|--------------|---------------|--------------|--------------|--------------|--------------|--|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム | |
| 2.5 | 70.0 | | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | | |
| 3.5 | 69.0 | 50.0 | | | | | | |
| 4.0 | 53.0 | 50.0 | 35.0 | | | | | |
| 4.5 | 42.6 | 42.3 | 35.0 | | | | | |
| 5.0 | 35.4 | 35.0 | 34.7 | 24.0 | | | | |
| 6.0 | 25.9 | 25.5 | 25.1 | 24.0 | | | | |
| 7.0 | 20.0 | 19.5 | 19.2 | 20.8 | 17.0 | 14.0 | | |
| 8.0 | 16.0 | 15.4 | 15.1 | 16.6 | 17.0 | 14.0 | 12.0 | |
| 9.0 | 13.0 | 12.4 | 12.1 | 13.5 | 14.4 | 14.0 | 12.0 | |
| 10.0 | | 10.1 | 9.8 | 11.2 | 12.0 | 12.3 | 12.0 | |
| 12.0 | | 6.9 | 6.6 | 7.9 | 8.7 | 8.9 | 9.1 | |
| 14.0 | | 4.7 | 4.4 | 5.6 | 6.4 | 6.6 | 6.8 | |
| 16.0 | | 3.2 | 2.8 | 4.0 | 4.8 | 5.0 | 5.2 | |
| 18.0 | | | | 2.8 | 3.5 | 3.8 | 3.9 | |
| 20.0 | | | | | 2.6 | 2.8 | 3.0 | |
| 危険角度(°) | — | — | 52 | 59 | 62 | 65 | 67 | |
| 標準フック | 70t | | | | 50t | | | |
| フック質量 | 900kg | | | | 600kg | | | |
| 巻掛本数 | 10 | 7 | 5 | | | 4 | | |

(単位 : ton)

SLジブ横抱

SLジブ無

KATO KA-1300R ブーム定格総荷重表 (SLジブ無)

| NC1性能 作業半径 (m) | アウトリガ最大 (8.4m) 張出 (全周) | | | | | | カウンタウエイト 8.5t | |
|----------------------|------------------------|--------------|---------------|--------------|--------------|--------------|---------------|--|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム | |
| 2.5 | 70.0 | | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | | |
| 4.5 | 70.0 | 50.0 | 35.0 | | | | | |
| 5.0 | 70.0 | 50.0 | 35.0 | 24.0 | | | | |
| 6.0 | 63.2 | 50.0 | 35.0 | 24.0 | | | | |
| 7.0 | 53.1 | 50.0 | 35.0 | 24.0 | 17.0 | 14.0 | | |
| 8.0 | 45.5 | 44.6 | 35.0 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 9.0 | 39.6 | 38.7 | 35.0 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 10.0 | | 34.0 | 33.6 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 12.0 | | 24.7 | 24.3 | 23.2 | 17.0 | 14.0 | 12.0 | |
| 14.0 | | 18.7 | 18.2 | 19.8 | 15.8 | 14.0 | 12.0 | |
| 16.0 | | 14.5 | 14.1 | 15.5 | 14.0 | 14.0 | 12.0 | |
| 18.0 | | | 11.0 | 12.5 | 12.6 | 13.1 | 12.0 | |
| 20.0 | | | 8.6 | 10.1 | 11.0 | 11.3 | 11.0 | |
| 22.0 | | | 6.5 | 8.1 | 9.0 | 9.4 | 9.8 | |
| 24.0 | | | 4.7 | 6.5 | 7.4 | 7.7 | 8.2 | |
| 26.0 | | | | 5.1 | 6.1 | 6.4 | 6.8 | |
| 28.0 | | | | 3.8 | 4.9 | 5.3 | 5.7 | |
| 30.0 | | | | 2.8 | 3.8 | 4.2 | 4.7 | |
| 32.0 | | | | 1.9 | 2.9 | 3.3 | 3.8 | |
| 34.0 | | | | | 2.2 | 2.5 | 3.0 | |
| 36.0 | | | | | 1.5 | 1.9 | 2.3 | |
| 38.0 | | | | | | 1.3 | 1.7 | |
| 40.0 | | | | | | | 1.1 | |
| 危険角度(°) | — | — | — | — | 32 | 35 | 38 | |
| 標準フック | 70t | | | | 50t | | | |
| フック質量 | 900kg | | | | 600kg | | | |
| 巻掛本数 | 10 | 7 | 5 | | | 4 | | |

(単位 : ton)

| NC2性能 作業半径 (m) | アウトリガ中間 (7.4m) 張出 (側方) | | | | | | カウンタウエイト 8.5t | |
|----------------------|------------------------|--------------|---------------|--------------|--------------|--------------|---------------|--|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム | |
| 2.5 | 70.0 | | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | | |
| 4.5 | 70.0 | 50.0 | 35.0 | | | | | |
| 5.0 | 70.0 | 50.0 | 35.0 | 24.0 | | | | |
| 6.0 | 62.2 | 50.0 | 35.0 | 24.0 | | | | |
| 7.0 | 53.1 | 50.0 | 35.0 | 24.0 | 17.0 | 14.0 | | |
| 8.0 | 45.5 | 44.6 | 35.0 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 9.0 | 36.4 | 35.1 | 34.8 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 10.0 | | 28.4 | 28.0 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 12.0 | | 19.8 | 19.4 | 21.0 | 17.0 | 14.0 | 12.0 | |
| 14.0 | | 14.6 | 14.2 | 15.7 | 15.8 | 14.0 | 12.0 | |
| 16.0 | | 11.0 | 10.6 | 12.0 | 12.9 | 13.2 | 12.0 | |
| 18.0 | | | 8.1 | 9.4 | 10.2 | 10.6 | 10.8 | |
| 20.0 | | | 6.1 | 7.5 | 8.2 | 8.5 | 8.8 | |
| 22.0 | | | 4.5 | 5.9 | 6.7 | 7.0 | 7.2 | |
| 24.0 | | | 3.0 | 4.7 | 5.4 | 5.7 | 6.0 | |
| 26.0 | | | | 3.5 | 4.4 | 4.7 | 4.9 | |
| 28.0 | | | | 2.4 | 3.4 | 3.8 | 4.1 | |
| 30.0 | | | | 1.5 | 2.5 | 2.9 | 3.2 | |
| 32.0 | | | | | 1.8 | 2.1 | 2.4 | |
| 34.0 | | | | | 1.1 | 1.5 | 1.8 | |
| 36.0 | | | | | | | 1.2 | |
| 危険角度(°) | — | — | — | 29 | 37 | 43 | 45 | |
| 標準フック | 70t | | | | 50t | | | |
| フック質量 | 900kg | | | | 600kg | | | |
| 巻掛本数 | 10 | 7 | 5 | | | 4 | | |

(単位 : ton)

KATO KA-1300R ブーム定格総荷重表 (SLジブ無)



| NC3性能 作業半径 (m) | アウトリガ中間 (6.4m) 張出 (側方) | | | | | | カウンタウエイト 8.5t | |
|----------------------|------------------------|--------------|---------------|--------------|--------------|--------------|---------------|--|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム | |
| 2.5 | 70.0 | | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | | |
| 4.5 | 70.0 | 50.0 | 35.0 | | | | | |
| 5.0 | 68.0 | 50.0 | 35.0 | 24.0 | | | | |
| 6.0 | 58.4 | 50.0 | 35.0 | 24.0 | | | | |
| 7.0 | 46.7 | 45.5 | 35.0 | 24.0 | 17.0 | 14.0 | | |
| 8.0 | 35.7 | 34.5 | 34.0 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 9.0 | 28.5 | 27.3 | 26.9 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 10.0 | | 22.3 | 21.8 | 23.5 | 17.0 | 14.0 | 12.0 | |
| 12.0 | | 15.5 | 15.1 | 16.6 | 17.0 | 14.0 | 12.0 | |
| 14.0 | | 11.3 | 10.9 | 12.3 | 13.2 | 13.5 | 12.0 | |
| 16.0 | | 8.4 | 8.0 | 9.4 | 10.2 | 10.5 | 10.8 | |
| 18.0 | | | 5.9 | 7.2 | 8.0 | 8.3 | 8.6 | |
| 20.0 | | | 4.0 | 5.5 | 6.3 | 6.6 | 6.9 | |
| 22.0 | | | 2.5 | 4.2 | 5.0 | 5.3 | 5.5 | |
| 24.0 | | | 1.2 | 2.9 | 3.9 | 4.2 | 4.5 | |
| 26.0 | | | | 1.8 | 2.8 | 3.2 | 3.5 | |
| 28.0 | | | | | 1.9 | 2.3 | 2.6 | |
| 30.0 | | | | | 1.2 | 1.5 | 1.9 | |
| 危険角度(°) | — | — | — | 41 | 45 | 50 | 52 | |
| 標準フック | 70t | | | | 50t | | | |
| フック質量 | 900kg | | | | 600kg | | | |
| 巻掛本数 | 10 | 7 | 5 | | | 4 | | |

(単位 : ton)

NA性能

NB性能

NC性能

ND性能

NE性能

| NC4性能 作業半径 (m) | アウトリガ中間 (5.4m) 張出 (側方) | | | | | | カウンタウエイト 8.5t | |
|----------------------|------------------------|--------------|---------------|--------------|--------------|--------------|---------------|--|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム | |
| 2.5 | 70.0 | | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | | |
| 4.5 | 68.8 | 50.0 | 35.0 | | | | | |
| 5.0 | 63.1 | 50.0 | 35.0 | 24.0 | | | | |
| 6.0 | 44.1 | 42.9 | 35.0 | 24.0 | | | | |
| 7.0 | 32.5 | 31.4 | 30.9 | 24.0 | 17.0 | 14.0 | | |
| 8.0 | 25.3 | 24.2 | 23.8 | 24.0 | 17.0 | 14.0 | 12.0 | |
| 9.0 | 20.4 | 19.3 | 18.9 | 20.5 | 17.0 | 14.0 | 12.0 | |
| 10.0 | | 15.7 | 15.3 | 16.8 | 17.0 | 14.0 | 12.0 | |
| 12.0 | | 10.9 | 10.5 | 11.9 | 12.7 | 13.0 | 12.0 | |
| 14.0 | | 7.8 | 7.4 | 8.7 | 9.4 | 9.7 | 10.0 | |
| 16.0 | | 5.6 | 5.2 | 6.4 | 7.2 | 7.5 | 7.7 | |
| 18.0 | | | 3.5 | 4.8 | 5.5 | 5.8 | 6.0 | |
| 20.0 | | | 1.9 | 3.5 | 4.2 | 4.5 | 4.7 | |
| 22.0 | | | | 2.3 | 3.2 | 3.5 | 3.7 | |
| 24.0 | | | | 1.2 | 2.2 | 2.6 | 2.8 | |
| 危険角度(°) | — | — | 40 | 46 | 54 | 57 | 60 | |
| 標準フック | 70t | | | | 50t | | | |
| フック質量 | 900kg | | | | 600kg | | | |
| 巻掛本数 | 10 | 7 | 5 | | | 4 | | |

(単位 : ton)

SLジブ横抱

SLジブ無

KATO KA-1300R ブーム定格総荷重表 (SLジブ無)

| NC5性能 | | アウトリガ中間 (4.4m) 張出 (側方) | | | | カウンタウエイト 8.5t | | |
|----------|--------------|------------------------|---------------|--------------|--------------|---------------|--------------|--|
| 作業半径 (m) | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム | |
| 2.5 | 70.0 | | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | | |
| 4.0 | 68.8 | 50.0 | 35.0 | | | | | |
| 4.5 | 55.7 | 50.0 | 35.0 | | | | | |
| 5.0 | 44.8 | 43.7 | 35.0 | 24.0 | | | | |
| 6.0 | 31.5 | 30.5 | 30.1 | 24.0 | | | | |
| 7.0 | 23.8 | 22.7 | 22.3 | 23.6 | 17.0 | 14.0 | | |
| 8.0 | 18.7 | 17.7 | 17.3 | 18.8 | 17.0 | 14.0 | 12.0 | |
| 9.0 | 15.1 | 14.1 | 13.7 | 15.1 | 15.9 | 14.0 | 12.0 | |
| 10.0 | | 11.4 | 11.0 | 12.4 | 13.2 | 13.5 | 12.0 | |
| 12.0 | | 7.7 | 7.3 | 8.6 | 9.3 | 9.6 | 9.9 | |
| 14.0 | | 5.2 | 4.8 | 6.1 | 6.8 | 7.1 | 7.3 | |
| 16.0 | | 3.5 | 2.9 | 4.3 | 5.0 | 5.3 | 5.5 | |
| 18.0 | | | | 2.9 | 3.7 | 3.9 | 4.1 | |
| 20.0 | | | | | 2.5 | 2.9 | 3.1 | |
| 危険角度(°) | — | — | 52 | 58 | 62 | 64 | 67 | |
| 標準フック | 70t | | | | | 50t | | |
| フック質量 | 900kg | | | | | 600kg | | |
| 巻掛本数 | 10 | 7 | 5 | | | 4 | | |

(単位 : ton)

| NC6性能 | | アウトリガ最小 (3.4m) 張出 (側方) | | | | カウンタウエイト 8.5t | | |
|----------|--------------|------------------------|---------------|--------------|--------------|---------------|--------------|--|
| 作業半径 (m) | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム | |
| 2.5 | 70.0 | | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | | |
| 3.5 | 56.3 | 50.0 | | | | | | |
| 4.0 | 43.0 | 41.8 | 35.0 | | | | | |
| 4.5 | 34.4 | 33.2 | 31.5 | | | | | |
| 5.0 | 28.4 | 27.3 | 26.9 | 24.0 | | | | |
| 6.0 | 20.5 | 19.5 | 19.1 | 20.5 | | | | |
| 7.0 | 15.6 | 14.6 | 14.3 | 15.6 | 16.0 | 14.0 | | |
| 8.0 | 12.2 | 11.3 | 11.0 | 12.2 | 13.0 | 13.1 | 12.0 | |
| 9.0 | 9.8 | 8.9 | 8.5 | 9.8 | 10.5 | 10.8 | 10.9 | |
| 10.0 | | 7.0 | 6.7 | 7.9 | 8.6 | 8.9 | 9.1 | |
| 12.0 | | 4.4 | 4.1 | 5.2 | 5.9 | 6.2 | 6.4 | |
| 14.0 | | 2.6 | | 3.4 | 4.1 | 4.3 | 4.6 | |
| 危険角度(°) | — | 39 | 62 | 65 | 69 | 71 | 73 | |
| 標準フック | 70t | | | | | 50t | | |
| フック質量 | 900kg | | | | | 600kg | | |
| 巻掛本数 | 10 | 7 | 5 | | | 4 | | |

(単位 : ton)

KATO KA-1300R ブーム定格総荷重表 (SLジブ無)



| ND1性能 作業半径 (m) | アウトリガ最大 (8.4m) 張出 (全周) | | | | カウンタウエイト ON キャリヤ 16t or 24t | | |
|----------------------|------------------------|--------------|---------------|--------------|-----------------------------|--------------|--------------|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム |
| 2.5 | 70.0 | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | |
| 4.5 | 70.0 | 50.0 | 35.0 | | | | |
| 5.0 | 70.0 | 50.0 | 35.0 | 24.0 | | | |
| 6.0 | 60.2 | 50.0 | 35.0 | 24.0 | | | |
| 7.0 | 50.2 | 49.1 | 35.0 | 24.0 | 17.0 | 14.0 | |
| 8.0 | 42.8 | 41.9 | 35.0 | 24.0 | 17.0 | 14.0 | 12.0 |
| 9.0 | 37.0 | 36.3 | 35.0 | 24.0 | 17.0 | 14.0 | 12.0 |
| 10.0 | | 31.8 | 31.4 | 24.0 | 17.0 | 14.0 | 12.0 |
| 12.0 | | 21.9 | 21.4 | 23.2 | 17.0 | 14.0 | 12.0 |
| 14.0 | | 15.3 | 14.9 | 16.8 | 15.8 | 14.0 | 12.0 |
| 16.0 | | 11.1 | 10.7 | 12.5 | 13.5 | 13.9 | 12.0 |
| 18.0 | | | 7.8 | 9.5 | 10.5 | 10.8 | 11.1 |
| 20.0 | | | 5.7 | 7.3 | 8.2 | 8.6 | 8.8 |
| 22.0 | | | 4.1 | 5.7 | 6.5 | 6.9 | 7.1 |
| 24.0 | | | 2.6 | 4.3 | 5.2 | 5.5 | 5.8 |
| 26.0 | | | | 3.2 | 4.1 | 4.4 | 4.7 |
| 28.0 | | | | 2.1 | 3.2 | 3.5 | 3.8 |
| 30.0 | | | | 1.2 | 2.3 | 2.7 | 3.0 |
| 32.0 | | | | | 1.5 | 1.9 | 2.2 |
| 34.0 | | | | | | 1.2 | 1.5 |
| 危険角度(°) | — | — | — | 29 | 42 | 44 | 48 |
| 標準フック | 70t | 50t | | | | | |
| フック質量 | 900kg | 600kg | | | | | |
| 巻掛本数 | 10 | 7 | 5 | 4 | | | |

(単位 : ton)

NA性能

NB性能

NC性能

ND性能

NE性能

| ND2性能 作業半径 (m) | アウトリガ中間 (7.4m) 張出 (側方) | | | | カウンタウエイト ON キャリヤ 16t or 24t | | |
|----------------------|------------------------|--------------|---------------|--------------|-----------------------------|--------------|--------------|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム |
| 2.5 | 70.0 | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | |
| 4.5 | 70.0 | 50.0 | 35.0 | | | | |
| 5.0 | 70.0 | 50.0 | 35.0 | 24.0 | | | |
| 6.0 | 60.2 | 50.0 | 35.0 | 24.0 | | | |
| 7.0 | 50.2 | 49.1 | 35.0 | 24.0 | 17.0 | 14.0 | |
| 8.0 | 42.8 | 41.9 | 35.0 | 24.0 | 17.0 | 14.0 | 12.0 |
| 9.0 | 36.1 | 35.0 | 34.6 | 24.0 | 17.0 | 14.0 | 12.0 |
| 10.0 | | 28.3 | 27.9 | 24.0 | 17.0 | 14.0 | 12.0 |
| 12.0 | | 19.7 | 19.3 | 21.2 | 17.0 | 14.0 | 12.0 |
| 14.0 | | 14.5 | 14.1 | 15.8 | 15.8 | 14.0 | 12.0 |
| 16.0 | | 10.9 | 10.5 | 12.1 | 13.0 | 13.3 | 12.0 |
| 18.0 | | | 7.8 | 9.5 | 10.4 | 10.7 | 10.9 |
| 20.0 | | | 5.7 | 7.3 | 8.2 | 8.6 | 8.8 |
| 22.0 | | | 4.1 | 5.7 | 6.5 | 6.9 | 7.1 |
| 24.0 | | | 2.6 | 4.3 | 5.2 | 5.5 | 5.8 |
| 26.0 | | | | 3.2 | 4.1 | 4.4 | 4.7 |
| 28.0 | | | | 2.1 | 3.2 | 3.5 | 3.8 |
| 30.0 | | | | 1.2 | 2.3 | 2.7 | 3.0 |
| 32.0 | | | | | 1.5 | 1.9 | 2.2 |
| 34.0 | | | | | | 1.2 | 1.5 |
| 危険角度(°) | — | — | — | 30 | 42 | 44 | 48 |
| 標準フック | 70t | 50t | | | | | |
| フック質量 | 900kg | 600kg | | | | | |
| 巻掛本数 | 10 | 7 | 5 | 4 | | | |

(単位 : ton)

SLジブ横抱

SLジブ無

KATO KA-1300R ブーム定格総荷重表 (SLジブ無)

| ND3性能 | アウトリガ中間 (6.4m) 張出 (側方) | | | | カウンタウエイト ON キャリヤ 16t or 24t | | |
|----------|------------------------|--------------|---------------|--------------|-----------------------------|--------------|--------------|
| 作業半径 (m) | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム |
| 2.5 | 70.0 | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | |
| 4.5 | 70.0 | 50.0 | 35.0 | | | | |
| 5.0 | 70.0 | 50.0 | 35.0 | 24.0 | | | |
| 6.0 | 60.2 | 50.0 | 35.0 | 24.0 | | | |
| 7.0 | 45.6 | 44.4 | 35.0 | 24.0 | 17.0 | 14.0 | |
| 8.0 | 34.8 | 33.7 | 33.3 | 24.0 | 17.0 | 14.0 | 12.0 |
| 9.0 | 27.8 | 26.6 | 26.3 | 24.0 | 17.0 | 14.0 | 12.0 |
| 10.0 | | 21.7 | 21.3 | 23.2 | 17.0 | 14.0 | 12.0 |
| 12.0 | | 15.1 | 14.7 | 16.4 | 17.0 | 14.0 | 12.0 |
| 14.0 | | 10.9 | 10.6 | 12.2 | 13.0 | 13.4 | 12.0 |
| 16.0 | | 8.1 | 7.7 | 9.2 | 10.1 | 10.4 | 10.6 |
| 18.0 | | | 5.6 | 7.1 | 7.9 | 8.2 | 8.4 |
| 20.0 | | | 3.8 | 5.4 | 6.2 | 6.5 | 6.7 |
| 22.0 | | | 2.2 | 4.1 | 4.9 | 5.2 | 5.4 |
| 24.0 | | | | 2.8 | 3.8 | 4.1 | 4.4 |
| 26.0 | | | | 1.7 | 2.8 | 3.1 | 3.4 |
| 28.0 | | | | | 1.9 | 2.2 | 2.5 |
| 30.0 | | | | | 1.1 | 1.5 | 1.8 |
| 危険角度(°) | — | — | 33 | 41 | 45 | 50 | 54 |
| 標準フック | 70t | | | | 50t | | |
| フック質量 | 900kg | | | | 600kg | | |
| 巻掛本数 | 10 | 7 | 5 | | | 4 | |

(単位 : ton)

| ND4性能 | アウトリガ中間 (5.4m) 張出 (側方) | | | | カウンタウエイト ON キャリヤ 16t or 24t | | |
|----------|------------------------|--------------|---------------|--------------|-----------------------------|--------------|--------------|
| 作業半径 (m) | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム |
| 2.5 | 70.0 | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | |
| 4.5 | 67.7 | 50.0 | 35.0 | | | | |
| 5.0 | 62.2 | 50.0 | 35.0 | 24.0 | | | |
| 6.0 | 42.2 | 41.0 | 35.0 | 24.0 | | | |
| 7.0 | 31.1 | 29.9 | 29.6 | 24.0 | 17.0 | 14.0 | |
| 8.0 | 24.1 | 23.0 | 22.7 | 24.0 | 17.0 | 14.0 | 12.0 |
| 9.0 | 19.4 | 18.3 | 18.0 | 19.8 | 17.0 | 14.0 | 12.0 |
| 10.0 | | 14.9 | 14.5 | 16.2 | 17.0 | 14.0 | 12.0 |
| 12.0 | | 10.2 | 9.9 | 11.4 | 12.2 | 12.5 | 12.0 |
| 14.0 | | 7.2 | 6.9 | 8.3 | 9.1 | 9.4 | 9.6 |
| 16.0 | | 5.1 | 4.7 | 6.1 | 6.9 | 7.1 | 7.4 |
| 18.0 | | | 3.0 | 4.5 | 5.2 | 5.5 | 5.7 |
| 20.0 | | | 1.4 | 3.2 | 4.0 | 4.2 | 4.4 |
| 22.0 | | | | 2.0 | 3.0 | 3.2 | 3.4 |
| 24.0 | | | | | 1.9 | 2.3 | 2.6 |
| 危険角度(°) | — | — | 40 | 50 | 56 | 59 | 61 |
| 標準フック | 70t | | | | 50t | | |
| フック質量 | 900kg | | | | 600kg | | |
| 巻掛本数 | 10 | 7 | 5 | | | 4 | |

(単位 : ton)

KATO KA-1300R ブーム定格総荷重表 (SLジブ無)



| ND5性能 作業半径 (m) | アウトリガ中間 (4.4m) 張出 (側方) | | | | カウンタウエイト ON キャリヤ 16t or 24t | | |
|----------------------|------------------------|--------------|---------------|--------------|-----------------------------|--------------|--------------|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム |
| 2.5 | 70.0 | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | |
| 4.0 | 67.5 | 50.0 | 35.0 | | | | |
| 4.5 | 52.0 | 50.0 | 35.0 | | | | |
| 5.0 | 41.7 | 40.6 | 35.0 | 24.0 | | | |
| 6.0 | 29.3 | 28.2 | 27.9 | 24.0 | | | |
| 7.0 | 22.0 | 20.9 | 20.7 | 22.0 | 17.0 | 14.0 | |
| 8.0 | 17.2 | 16.2 | 15.9 | 17.6 | 17.0 | 14.0 | 12.0 |
| 9.0 | 13.8 | 12.8 | 12.5 | 14.1 | 14.9 | 14.0 | 12.0 |
| 10.0 | | 10.3 | 10.0 | 11.5 | 12.3 | 12.6 | 12.0 |
| 12.0 | | 6.8 | 6.5 | 7.9 | 8.7 | 9.0 | 9.2 |
| 14.0 | | 4.5 | 4.2 | 5.5 | 6.2 | 6.5 | 6.7 |
| 16.0 | | 2.6 | 2.1 | 3.8 | 4.5 | 4.8 | 5.0 |
| 18.0 | | | | 2.3 | 3.2 | 3.5 | 3.7 |
| 危険角度(°) | — | — | 52 | 59 | 65 | 67 | 69 |
| 標準フック | 70t | 50t | | | | | |
| フック質量 | 900kg | 600kg | | | | | |
| 巻掛本数 | 10 | 7 | 5 | 4 | | | |

(単位 : ton)

NA性能

NB性能

NC性能

ND性能

NE性能

| ND6性能 作業半径 (m) | アウトリガ最小 (3.4m) 張出 (側方) | | | | カウンタウエイト ON キャリヤ 16t or 24t | | |
|----------------------|------------------------|--------------|---------------|--------------|-----------------------------|--------------|--------------|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム |
| 2.5 | 70.0 | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | |
| 3.5 | 50.6 | 47.5 | | | | | |
| 4.0 | 38.5 | 37.3 | 32.9 | | | | |
| 4.5 | 30.7 | 29.6 | 27.8 | | | | |
| 5.0 | 25.2 | 24.2 | 23.8 | 23.4 | | | |
| 6.0 | 18.1 | 17.1 | 16.9 | 18.2 | | | |
| 7.0 | 13.6 | 12.7 | 12.4 | 14.0 | 14.3 | 14.0 | |
| 8.0 | 10.6 | 9.7 | 9.4 | 10.9 | 11.6 | 11.6 | 11.5 |
| 9.0 | 8.4 | 7.5 | 7.2 | 8.6 | 9.4 | 9.6 | 9.5 |
| 10.0 | | 5.8 | 5.5 | 6.8 | 7.6 | 7.9 | 8.0 |
| 12.0 | | 3.4 | 3.1 | 4.4 | 5.1 | 5.4 | 5.5 |
| 14.0 | | 1.5 | | | | | |
| 危険角度(°) | — | 39 | 62 | 69 | 73 | 74 | 76 |
| 標準フック | 70t | 50t | | | | | |
| フック質量 | 900kg | 600kg | | | | | |
| 巻掛本数 | 10 | 7 | 5 | 4 | | | |

(単位 : ton)

SLジブ横抱

SLジブ無

KATO KA-1300R ブーム定格総荷重表 (SLジブ無)

| NE1性能 作業半径 (m) | アウトリガ最大 (8.4m) 張出 (全周) | | | | カウンタウエイト ON キャリヤ 0t or 8.5t | | |
|----------------------|------------------------|--------------|---------------|--------------|-----------------------------|--------------|--------------|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム |
| 2.5 | 70.0 | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | |
| 4.5 | 70.0 | 50.0 | 35.0 | | | | |
| 5.0 | 70.0 | 50.0 | 35.0 | 24.0 | | | |
| 6.0 | 60.2 | 50.0 | 35.0 | 24.0 | | | |
| 7.0 | 50.2 | 49.1 | 35.0 | 24.0 | 17.0 | 14.0 | |
| 8.0 | 41.1 | 39.9 | 35.0 | 24.0 | 17.0 | 14.0 | 12.0 |
| 9.0 | 32.9 | 31.7 | 31.4 | 24.0 | 17.0 | 14.0 | 12.0 |
| 10.0 | | 26.0 | 25.6 | 24.0 | 17.0 | 14.0 | 12.0 |
| 12.0 | | 18.4 | 18.0 | 19.8 | 17.0 | 14.0 | 12.0 |
| 14.0 | | 13.4 | 12.9 | 14.9 | 15.8 | 14.0 | 12.0 |
| 16.0 | | 9.6 | 9.1 | 10.9 | 11.9 | 12.3 | 12.0 |
| 18.0 | | | 6.5 | 8.2 | 9.1 | 9.5 | 9.8 |
| 20.0 | | | 4.6 | 6.2 | 7.1 | 7.4 | 7.7 |
| 22.0 | | | 2.9 | 4.6 | 5.5 | 5.8 | 6.1 |
| 24.0 | | | 1.4 | 3.4 | 4.3 | 4.6 | 4.9 |
| 26.0 | | | | 2.2 | 3.3 | 3.6 | 3.9 |
| 28.0 | | | | 1.2 | 2.3 | 2.7 | 3.0 |
| 30.0 | | | | | 1.4 | 1.8 | 2.2 |
| 危険角度(°) | — | — | — | 36 | 46 | 50 | 54 |
| 標準フック | 70t | 50t | | | | | |
| フック質量 | 900kg | 600kg | | | | | |
| 巻掛本数 | 10 | 7 | 5 | 4 | | | |

(単位 : ton)

| NE2性能 作業半径 (m) | アウトリガ中間 (7.4m) 張出 (側方) | | | | カウンタウエイト ON キャリヤ 0t or 8.5t | | |
|----------------------|------------------------|--------------|---------------|--------------|-----------------------------|--------------|--------------|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム |
| 2.5 | 70.0 | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | |
| 4.5 | 70.0 | 50.0 | 35.0 | | | | |
| 5.0 | 70.0 | 50.0 | 35.0 | 24.0 | | | |
| 6.0 | 60.2 | 50.0 | 35.0 | 24.0 | | | |
| 7.0 | 49.4 | 48.1 | 35.0 | 24.0 | 17.0 | 14.0 | |
| 8.0 | 36.5 | 35.3 | 34.6 | 24.0 | 17.0 | 14.0 | 12.0 |
| 9.0 | 28.5 | 27.3 | 26.9 | 24.0 | 17.0 | 14.0 | 12.0 |
| 10.0 | | 21.8 | 21.4 | 23.5 | 17.0 | 14.0 | 12.0 |
| 12.0 | | 14.8 | 14.4 | 16.2 | 17.0 | 14.0 | 12.0 |
| 14.0 | | 10.5 | 10.1 | 11.8 | 12.7 | 13.0 | 12.0 |
| 16.0 | | 7.6 | 7.2 | 8.8 | 9.7 | 10.0 | 10.2 |
| 18.0 | | | 5.1 | 6.6 | 7.5 | 7.8 | 8.0 |
| 20.0 | | | 3.2 | 5.0 | 5.8 | 6.1 | 6.3 |
| 22.0 | | | 1.7 | 3.5 | 4.5 | 4.8 | 5.0 |
| 24.0 | | | | 2.3 | 3.4 | 3.7 | 4.0 |
| 26.0 | | | | 1.2 | 2.3 | 2.7 | 3.0 |
| 28.0 | | | | | 1.4 | 1.8 | 2.1 |
| 危険角度(°) | — | — | 33 | 41 | 49 | 53 | 57 |
| 標準フック | 70t | 50t | | | | | |
| フック質量 | 900kg | 600kg | | | | | |
| 巻掛本数 | 10 | 7 | 5 | 4 | | | |

(単位 : ton)

KATO KA-1300R ブーム定格総荷重表 (SLジブ無)



| NE3性能 作業半径 (m) | アウトリガ中間 (6.4m) 張出 (側方) | | | | カウンタウエイト ON キャリヤ 0t or 8.5t | | |
|----------------------|------------------------|--------------|---------------|--------------|-----------------------------|--------------|--------------|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム |
| 2.5 | 70.0 | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | |
| 4.5 | 70.0 | 50.0 | 35.0 | | | | |
| 5.0 | 66.3 | 50.0 | 35.0 | 24.0 | | | |
| 6.0 | 51.6 | 50.0 | 35.0 | 24.0 | | | |
| 7.0 | 36.5 | 35.1 | 33.0 | 24.0 | 17.0 | 14.0 | |
| 8.0 | 27.6 | 26.3 | 25.9 | 24.0 | 17.0 | 14.0 | 12.0 |
| 9.0 | 21.8 | 20.5 | 20.2 | 21.7 | 17.0 | 14.0 | 12.0 |
| 10.0 | | 16.4 | 16.1 | 18.0 | 17.0 | 14.0 | 12.0 |
| 12.0 | | 11.1 | 10.7 | 12.4 | 13.3 | 13.4 | 12.0 |
| 14.0 | | 7.7 | 7.3 | 8.9 | 9.8 | 10.1 | 10.2 |
| 16.0 | | 5.3 | 4.9 | 6.4 | 7.3 | 7.6 | 7.8 |
| 18.0 | | | 2.8 | 4.7 | 5.5 | 5.8 | 6.0 |
| 20.0 | | | 1.2 | 3.1 | 4.1 | 4.4 | 4.6 |
| 22.0 | | | | 1.8 | 2.8 | 3.2 | 3.5 |
| 24.0 | | | | | | 2.1 | |
| 危険角度(°) | — | — | 40 | 50 | 58 | 59 | 64 |
| 標準フック | 70t | | | | 50t | | |
| フック質量 | 900kg | | | | 600kg | | |
| 巻掛本数 | 10 | 7 | 5 | | | 4 | |

(単位 : ton)

NE性能
NA性能
NB性能
NC性能
ND性能
NE性能

| NE4性能 作業半径 (m) | アウトリガ中間 (5.4m) 張出 (側方) | | | | カウンタウエイト ON キャリヤ 0t or 8.5t | | |
|----------------------|------------------------|--------------|---------------|--------------|-----------------------------|--------------|--------------|
| | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム |
| 2.5 | 70.0 | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | |
| 4.0 | 70.0 | 50.0 | 35.0 | | | | |
| 4.5 | 66.8 | 50.0 | 35.0 | | | | |
| 5.0 | 51.1 | 49.7 | 35.0 | 24.0 | | | |
| 6.0 | 34.0 | 32.7 | 31.2 | 24.0 | | | |
| 7.0 | 24.7 | 23.6 | 23.3 | 24.0 | 17.0 | 14.0 | |
| 8.0 | 19.0 | 17.9 | 17.6 | 19.4 | 17.0 | 14.0 | 12.0 |
| 9.0 | 15.0 | 14.0 | 13.6 | 15.3 | 15.9 | 14.0 | 12.0 |
| 10.0 | | 11.1 | 10.8 | 12.4 | 13.3 | 13.4 | 12.0 |
| 12.0 | | 7.3 | 6.9 | 8.4 | 9.2 | 9.5 | 9.8 |
| 14.0 | | 4.8 | 4.4 | 5.8 | 6.6 | 6.9 | 7.1 |
| 16.0 | | 2.9 | 2.4 | 4.0 | 4.8 | 5.0 | 5.3 |
| 18.0 | | | | 2.5 | 3.4 | 3.7 | 3.9 |
| 危険角度(°) | — | — | 52 | 58 | 65 | 67 | 69 |
| 標準フック | 70t | | | | 50t | | |
| フック質量 | 900kg | | | | 600kg | | |
| 巻掛本数 | 10 | 7 | 5 | | | 4 | |

(単位 : ton)

SLジブ横抱
SLジブ無

KATO KA-1300R ブーム定格総荷重表 (SLジブ無)

| NE5性能 | アウトリガ中間 (4.4m) 張出 (側方) | | | | カウンタウエイト ON キャリヤ 0t or 8.5t | | |
|----------|------------------------|--------------|---------------|--------------|-----------------------------|--------------|--------------|
| 作業半径 (m) | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | 44.0m ブーム | 48.0m ブーム | 52.0m ブーム |
| 2.5 | 70.0 | | | | | | |
| 3.0 | 70.0 | 50.0 | | | | | |
| 3.5 | 70.0 | 50.0 | | | | | |
| 4.0 | 55.7 | 49.1 | 35.0 | | | | |
| 4.5 | 42.4 | 40.3 | 34.0 | | | | |
| 5.0 | 33.9 | 32.5 | 28.8 | 24.0 | | | |
| 6.0 | 23.4 | 22.2 | 21.3 | 21.4 | | | |
| 7.0 | 17.3 | 16.2 | 15.9 | 16.8 | 16.6 | 14.0 | |
| 8.0 | 13.3 | 12.2 | 11.9 | 13.5 | 13.5 | 13.4 | 12.0 |
| 9.0 | 10.5 | 9.4 | 9.1 | 10.7 | 11.1 | 11.1 | 11.0 |
| 10.0 | | 7.4 | 7.0 | 8.5 | 9.2 | 9.2 | 9.2 |
| 12.0 | | 4.5 | 4.1 | 5.5 | 6.3 | 6.4 | 6.5 |
| 14.0 | | 2.3 | | 3.5 | 4.2 | 4.4 | 4.5 |
| 危険角度(°) | — | 39 | 62 | 65 | 70 | 72 | 73 |
| 標準フック | 70t | 50t | | | | | |
| フック質量 | 900kg | 600kg | | | | | |
| 巻掛本数 | 10 | 7 | 5 | | 4 | | |

(単位 : ton)

| NE6性能 | アウトリガ最小 (3.4m) 張出 (側方) | | | カウンタウエイト ON キャリヤ 0t or 8.5t | |
|----------|------------------------|--------------|---------------|-----------------------------|--|
| 作業半径 (m) | 11.8m ブーム | 19.8m ブーム | 27.88m ブーム | 35.9m ブーム | |
| 2.5 | 70.0 | | | | |
| 3.0 | 59.7 | 48.7 | | | |
| 3.5 | 41.8 | 38.4 | | | |
| 4.0 | 31.6 | 30.4 | 26.0 | | |
| 4.5 | 25.0 | 23.9 | 21.7 | | |
| 5.0 | 20.4 | 19.3 | 18.4 | 18.3 | |
| 6.0 | 14.4 | 13.4 | 13.2 | 13.8 | |
| 7.0 | 10.6 | 9.7 | 9.4 | 10.6 | |
| 8.0 | 8.1 | 7.1 | 6.9 | 8.2 | |
| 9.0 | 6.2 | 5.3 | 5.0 | 6.3 | |
| 10.0 | | 3.9 | | 4.8 | |
| 12.0 | | 1.5 | | | |
| 危険角度(°) | — | 48 | 69 | 72 | |
| 標準フック | 70t | 50t | | | |
| フック質量 | 900kg | 600kg | | | |
| 巻掛本数 | 10 | 7 | 5 | 4 | |

(単位 : ton)